


PM 37-500_p on



Luminary

Luminária

- L70 > 50000h
- MacAdam 3
- UGR <19

LED/Optic Óptica

- COB LUMINUS
- Lens

Driver

- Included

Voltage Voltaje

- 220-240VAC

Dimming Regulación

- ON-OFF
- PH-CUT

Protection Protección

- IP20

Accessories Accesorios

- Honeycomb
Panel de abeja

Basic finishes

Acabados básicos

- Black
- White

Special finishes

Acabados especiales

NCS

- Oliva - S 7010-G30Y
- Ocre - S 5040-Y70R
- Terracota - S 3050-Y60R
- Mocha - S 5010-Y10R
- Sand - S 2005-Y50R

Metallic Metálico

- Gun Metal
- Bronze
- Brushed Copper
- Old Silver
- Cava

Downloads Descargas



Cod.	W	Beam angle	CRI	K	Lm	Efficiency
8950.I2700710.x	8,2W	10°	95	2700K	527Lm	65Lm/W
8950.I2700715.x	8,2W	15°	95	2700K	527Lm	65Lm/W
8950.I2700724.x	8,2W	24°	95	2700K	527Lm	65Lm/W
8950.I2700736.x	8,2W	36°	95	2700K	527Lm	65Lm/W
8950.I2700750.x	8,2W	50°	95	2700K	527Lm	65Lm/W
8950.I3000710.x	8,2W	10°	95	3000K	547Lm	67Lm/W
8950.I3000715.x	8,2W	15°	95	3000K	547Lm	67Lm/W
8950.I3000724.x	8,2W	24°	95	3000K	547Lm	67Lm/W
8950.I3000736.x	8,2W	36°	95	3000K	547Lm	67Lm/W
8950.I3000750.x	8,2W	50°	95	3000K	547Lm	67Lm/W
8950.I4000710.x	8,2W	10°	95	4000K	574Lm	70Lm/W
8950.I4000715.x	8,2W	15°	95	4000K	574Lm	70Lm/W
8950.I4000724.x	8,2W	24°	95	4000K	574Lm	70Lm/W
8950.I4000736.x	8,2W	36°	95	4000K	574Lm	70Lm/W
8950.I4000750.x	8,2W	50°	95	4000K	574Lm	70Lm/W



Ask for recessed base.
Base de empotrar, consultar.

