

PM 111_trk mag



Luminary

Luminária

- L70 > 50000h
- MacAdam 3

LED/Optic Óptica

- COB LUMINUS
- Lens

Voltage Voltaje

- 48VDC

Dimming Regulación

- ON-OFF
- PUSH ONLY
- DALI-2

Protection Protección

- IP20

Accessories Accesorios

- Honeycomb (included)
Panal de abeja (incluido)

Basic finishes

Acabados básicos

- Black
- White

Special finishes

Acabados especiales

NCS

- Oliva - S 7010-G30Y
- Ocre - S 5040-Y70R
- Terracota - S 3050-Y60R
- Mocha - S 5010-Y10R
- Sand - S 2005-Y50R

Metallic Metálico

- Gun Metal
- Bronze
- Brushed Copper
- Old Silver
- Cava

Downloads Descargas



Cod.	W	Beam angle	CRI	K	Lm	Efficiencie
6211.927018HA.x	20,7W	HC15°	90	2700K	1464Lm	71Lm/W
6211.927018HC.x	20,7W	HC36°	90	2700K	1464Lm	71Lm/W
6211.930018HA.x	20,7W	HC15°	90	3000K	1579Lm	77Lm/W
6211.930018HC.x	20,7W	HC36°	90	3000K	1579Lm	77Lm/W
6211.940018HA.x	20,7W	HC15°	90	4000K	1698Lm	82Lm/W
6211.940018HC.x	20,7W	HC36°	90	4000K	1698Lm	82Lm/W

