

PM 46_in dl zoom



Luminary

Luminària

- L70 > 50000h
- MacAdam 3

LED/Optic Òptica

- COB LUMINUS
- COB BRIDGELUX (Tunable White)
- Lens

Voltage Voltaje

- 220-240VAC

Dimming Regulación

- ON-OFF
- PH-CUT
- 1-10V
- PUSH ONLY
- DALI-2

Tunable White

Dimming Regulación

- NO DRIVER
- DALI DT8

Protection Protección

- IP20

Basic finishes

Acabados básicos

- Black
- White

Special finishes

Acabados especiales

NCS

- Oliva - S 7010-G30Y
- Ocre - S 5040-Y70R
- Terracota - S 3050-Y60R
- Mocha - S 5010-Y10R
- Sand - S 2005-Y50R

Metallic Metálico

- Gun Metal
- Bronze
- Brushed Copper
- Old Silver
- Cava

Downloads Descargas



Cod.	W	Beam angle	CRI	K	Lm	Efficiency
2261.I27007ZM.x	8,2W	16-45°	95	2700K	422Lm	52Lm/W
2261.I30007ZM.x	8,2W	16-45°	95	3000K	438Lm	54Lm/W
2261.I40007ZM.x	8,2W	16-45°	95	4000K	460Lm	57Lm/W

Tunable White

2261.TWB005ZM.x	6,2W	16-45°	90	1800-4000K	-	-
-----------------	------	--------	----	------------	---	---

