


PM 33_in dl+



Luminary

Luminária

- L70 > 50000h
- MacAdam 3

LED/Optic Óptica

- COB LUMINUS
- COB BRIDGELUX (Tunable White)
- Lens

Voltage Voltaje

- 220-240VAC

Dimming Regulación

- ON-OFF
- PH-CUT
- 1-10V
- PUSH ONLY
- DALI-2

Tunable White

Dimming Regulación

- NO-DRV
- DT8

Protection Protección

- IP20

Accessories Accesorios

- Honeycomb
- Panel de abeja

Basic finishes

Acabados básicos

- Black
- White

Special finishes

Acabados especiales

NCS

- Oliva - S 7010- G30Y
- Ocre - S 5040-Y70R
- Terracota - S 3050-Y60R
- Mocha - S 5010- Y10R
- Sand - S 2005-Y50R

Metallic Metálico

- Gun Metal
- Bronze
- Brushed Copper
- Old Silver
- Cava

Downloads Descargas



Cod.	W	Beam angle	CRI	K	Lm	Efficiencie
2246.I2700710. x	8,2W	10°	95	2700K	527Lm	65Lm/W
2246.I2700715. x	8,2W	15°	95	2700K	527Lm	65Lm/W
2246.I2700724. x	8,2W	24°	95	2700K	527Lm	65Lm/W
2246.I2700736. x	8,2W	36°	95	2700K	527Lm	65Lm/W
2246.I2700750. x	8,2W	50°	95	2700K	527Lm	65Lm/W
2246.I3000710. x	8,2W	10°	95	3000K	547Lm	67Lm/W
2246.I3000715. x	8,2W	15°	95	3000K	547Lm	67Lm/W
2246.I3000724. x	8,2W	24°	95	3000K	547Lm	67Lm/W
2246.I3000736. x	8,2W	36°	95	3000K	547Lm	67Lm/W
2246.I3000750. x	8,2W	50°	95	3000K	547Lm	67Lm/W
2246.I4000710. x	8,2W	10°	95	4000K	574Lm	70Lm/W
2246.I4000715. x	8,2W	15°	95	4000K	574Lm	70Lm/W
2246.I4000724. x	8,2W	24°	95	4000K	574Lm	70Lm/W
2246.I4000736. x	8,2W	36°	95	4000K	574Lm	70Lm/W
2246.I4000750. x	8,2W	50°	95	4000K	574Lm	70Lm/W

Tunable White

2246.TWB00515. x	6,2W	15°	90	1800-4000K	275-450Lm	45-73Lm/W
2246.TWB00524.x	6,2W	24°	90	1800-4000K	275-450Lm	45-73Lm/W
2246.TWB00536.x	6,2W	36°	90	1800-4000K	275-450Lm	45-73Lm/W
2246.TWB00550.x	6,2W	50°	90	1800-4000K	275-450Lm	45-73Lm/W

